

Ελάχιστο Μέγιστο Κέρδος εξόδου (50 DBSPL-max): 81 dB  
(Full of gain -max)

Ελάχιστο Μέγιστο Κέρδος εξόδου (50 DBSPL-HFA): 75 dB  
(Full of gain - HFA)

Ελάχιστη Μεγίστη έξοδος (90 DBSPL-max): 139 dB SPL  
(Maximum power output- max)

Ελάχιστη Μεγίστη έξοδος (90 DBSPL-HFA): 131 dB SPL  
(Maximum power output- HFA)

Spec Sheet Standard: IEC 118-7

Specification		Measurement	Unit
Reference Test Gain (60 dB SPL input)	HFA	54	dB
Full on Gain (50 dB SPL input)	Max.	81	dB
Full on Gain (50 dB SPL input)	HFA	75	dB
Maximum Output (90 dB SPL Input)	Max.	139	dB SPL
Maximum Output (90 dB SPL Input)	HFA	131	dB SPL
Total Harmonic Distortion	500 Hz	1.5	%
Total Harmonic Distortion	800 Hz	0.7	%
Total Harmonic Distortion	1600 Hz	0.4	%
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	114	dB SPL
Full-on Telecoil sensitivity @1 mA/m	HFA	106	dB SPL
Equivalent Input Noise w/o Noise reduction		23	dB SPL
Frequency Range	ANSI	100 - 4850	Hz
Current Drain (Quiescent / Operating)		1.1 / 1.7	mA
Battery Size		675	
Typical Battery Life Time		371	Hours